


| Acceptance Table - Barry Docks - 2024   |  |   |   |
|---|--|---|---|
| For a dock level of 10.00 metres  |  |   |   |
|   | Vessels may be accepted by Cardiff LPS up to the <b>draft</b> indicated without referral to the Harbour Master.  | Vessels may be accepted by Cardiff LPS up to the <b>length</b> indicated without referral to the Harbour Master | Vessels may be accepted by Cardiff LPS up to the <b>beam</b> indicated without referral to the Harbour Master                   |
|   | <b>Lady Windsor Lock</b>   |   |   |
| Lock  | Refer to berth   | 8.0m  | 19.20 metres  |
|   | <b>Number 1 Dock</b>   |   |   |
| Enterprise Quay 1   | Refer to Harbourmaster   |   | 19.20 metres  |
| Enterprise Quay 2   |  |   |   |
| Enterprise Quay 3   |  |   |   |
|   |  |   |   |
|   | <b>Juction Cut</b>   |   |   |
| Juction Cut   |  |   | 19.2 metres   |
|   | <b>Number 2 Dock</b>   |   |   |
| Cross Berth   | 7.5m   | 90m   | 19.20 metres  |
| 1 Berth (A Shed)  | 8.0m   | 140m  |   |
| 2 Berth   |  |   |   |
| 3 Berth (B Shed)  |  |   |   |
| 4 Berth   |  |   |   |
| 5 Berth   |  |   |   |
| 6 Berth   |  |   |   |
| 7 Berth   |  |   |   |
| 8 berth   |  |   |   |
| 9 Berth   | 8.0m   |   |   |
| 31 Berth  | 7.5m   |   |   |
|   | <b>Number 3 Dock</b>   |   |   |
| C Shed: via Lady Windsor Lock   | Refer to Harbourmaster   |   | 19.20 metres  |
| C Shed: via Basin entrance  | Refer to Harbourmaster   |   | 20.00 metres  |
| <b>Number 3 Dock - NOTE</b>   |  |   |   |
| The entrance to Number 3 Dock is 'U' shaped which means that as the beam of the vessel increases the draft must decrease to clear the invert. The table below |  |   |   |
| Please refer all enquiries regarding No3 dock to Harbourmaster.   | Max beam in metres   | Max Length  | Deduction from the predicted height of high water (ACD) to determine max acceptable draft [up to a maximum draft of 9.2 metres] |
| Number 3 Dock - Invert restrictions upon draft.   | <23.00   | 160m  | 2.38  |
|   | 23.00  |   | 2.38  |
|   | 23.10  |   | 2.48  |
|   | 23.20  |   | 2.58  |
|   | 23.40  |   | 2.78  |
|   | 23.50  |   | 2.83  |
|   | 23.60  |   | 2.93  |
|   | 23.80  |   | 3.08  |
|   | 23.90  |   | 3.18  |
|   | 24.00  |   | 3.28  |
| Other Areas of the Dock   | Vessels destined for areas of the dock which are not mentioned specifically in the table above should be referred to the Harbour   |   |   |
| Dock Level  | The dock level can not be maintained by impounding. On spring tides the level can rise to 11.9 metres and on neap tides it can fall to 9.00 metres. The average level is 10.00 metres. |   |   |
| Dock Water Density  | Average 1019   |   |   |
| Stemming Allowance  | Lady Windsor Lock and No 3 Dock (Basin)  | Please refer to latest Notice to Masters  |   |
| Specific berth acceptance draft is at all times subject to the predicted tide height and the application of the advertised stemming allowance                 |  |   |   |
| Version : 2.0   | Authorised :    | Version Date : 15/03/2024   | Owner : HM/DHM  |