

Acceptance Table - Newport Docks - February 2018

For a dock level of 11.74 metres

	Vessels may be accepted by Cardiff LPS up to the draft indicated without referral to the Harbour Master	Vessels may be accepted by Cardiff LPS up to the beam indicated without referral to the Harbour Master	Vessels may be accepted by Cardiff LPS up to the Length indicated without referral to the Harbour Master
	South Lock		
Lock	Refer to Berth	28m	200m
	South Dock		
1 Section	8m	28 m	200m
2 Section	10m		
3 Section	10m		
4 Section	10m		
5 Section	10m		
6 Section	10m		
7 Section	10m		
8 Section	10m		
9 Section	10m		
10 Section	10m		
11 Section	9m		
12 Section	9m		
East Lock	6.5m	18m	
Junction Cut		16m	
	North Dock		
21 Section	7.0m	16m	122m
22 Section	7.0m		
23 Section	6.5m		
24 Section	7.0m		
25 Section	7.0m		
26 Section	6.5m		
Other Areas of the Dock	Vessels destined for areas of the dock which are not mentioned specifically in the table above should be referred to the Harbour Master for a limiting beam and/or draft.		
*BLU Code vessels	Vessels subject to the provisions of the BLU Code will need acceptance by the Quality Control Manager for cargo operations in addition to Marine acceptance.		
Dock Level	The dock level can not be guaranteed but will generally be held at the average level of 11.74m		
Dock Water Density	North Dock	1002	
	South Dock	1010	
Stemming Allowance in the Dredged Channel	Flood tide	Please refer to the latest Notice to Masters for the present Allowance	
	Ebb tide		
Specific berth acceptance draft is at all times subject to the predicted tide height and the application of the advertised stemming allowance.			

