

<b>Acceptance Tables - Swansea Dock- January 2015-ACD</b>					
Channel Maintenance Level 4.2m			Ferry Berth Maintenance Level 4.9m		
Cill Level 2.82m below ACD					
<b>Kings and Queens Docks</b>					
For a dock level of 10.5m above datum					
Max Draft 9.9m subject to dock level and tide height, less the following clearance over the cills					
Swansea Kings Lock – Invert restrictions upon draft	Beam (m)	Clearance (m)	Cut (m)	For stemming (m)	Min Tide Height @ 9.9m
	< 22.9	0.76	0.3	1.07	Draft – 1.8m (8.1m)
	22.9 – 25.3	0.92	0.3	1.22	Draft - 1.6m (8.3m)
	< 25.3	1.22	0.3	1.52	Draft – 1.3m 8.6m
Maximum Dimensions		26.22m Beam or 26.83m if vessel has good working Bow thruster			
Vessels required to take a second pilot (Advise Agents)					
Over 182.9m LOA or >24.39m When			a) Entering or leaving the Queens Dock		
			b) Departing Kings Dock		
			c) Entering the KG5 Dry Dock		
<b>Prince of Wales Dock</b>					
Datum 2m above the level of the Entrance Lock Inner Gauge zero			Normal water level 8.5m		